

- TGR / TGF



Necessary for Welding Operator



Ultralight and rechargeable Tungsten Grinder

Capacity : The minimum length of the electrode bar to be ground is 15mm

Included angle: 15° - 180°



- Using a rechargeable motor(Ultra-light)
 - Precise grinding, cutting and facing
 - Including the precision setting device
 - Usage of diamond wheel
 - Economic improvement by using double-sided and with cutting function
 - Select the diamond wheel roughness depending on the electrode bar specification
 - Automatic concentric function
 - Improved convenience by marking cut scale
- One-touch lock function is applied when changing diamond wheel
 - Two models, angle fixed type(S-TGF) and angle adjustable type(S-TGR)
 - Multi-function collet application
 - No need to use jig depending on the specification of electrode bar
 - Electrode bar can be sharpened, even if it is stuck when welding
 - Non-standard electrode bar is available
 - The minimum length of electrode bar to be ground is 15mm
- Machine Specifications

Model	Specification	
Common	Rating	10.8V, 2Ah
	Speed	19500RPM
 - TGR	Included angle	15° - 120°, 180°
	Capacity	0.5 ϕ - 3.2 ϕ
	Weight	0.89kg(including battery)
 - TGF	Included angle	15°, 22.5°, 30°, 36°, 45°, 60°, 90°, 120°, 180°
	Capacity	0.5 ϕ - 3.2 ϕ
	Weight	0.99kg(including battery)

- Wheel Specifications



Model	Electrode bar
S-TG_40RG	2.4 ϕ - 3.2 ϕ
S-TG_40SG	1.6 ϕ - 2.4 ϕ
S-TG_40FG	0.5 ϕ - 1.6 ϕ

- Design and specification of these products are the version as of January 2018.
- The data may be subject to change for product improvement without a prior notice.
- Be sure to read through safety precautions described in the user manual and the equipment before using the products.